

22-6 Shielded Non-Plenum

ETL listed for guaranteed performance Made in the USA

Conductor

Drain

Jacket

Insulation

Shield

Applications:

Part No.: 900946

This document establishes the specifications for a six conductor shielded cable used for communication applications.

Construction Details:

Number of Conductors:6 Conductor: 22AWG Stranded bare copper Insulation Material: Polyvinyl Chloride Nominal Insulation Thickness: 0.008" Nominal Insulation Diameter: 0.045" Color code: Black, White, Red, Green, Blue, Brown Shielding: Overall Aluminum/Polyester (100% coverage) Drain: Stranded tin copper Jacket material: Polyvinyl Chloride Nominal Jacket thickness: 0.015" Nominal Diameter: 0.170" Surface Print:3122598 CMR 22AWG C(ETL)US FT4 + Sequential Footage Marking

Electricals:

Suggested working voltage: 300 Volts, rms.

Technical Details:

Temperature Rating

Operation

Nominal Weight:

23lbs.

Standards:

- NEC Article 800
- UL Subject 444, Type CM

Codes & Listings:

C(ETL)US

Preparation for Shipment:

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.



Issue Date: 06/15 Revision: 2 All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC .

1751 State RTE. 17A STE #1 Florida, NY 10921Customer Service: 800-431-3864Fax: 845-651-4160Website: www.remee.com



Part No.: 900946

22-6 Shielded Non-Plenum

ETL listed for guaranteed performance Made in the USA

Note: While Remee Products Corp. has made every reasonable effort to ensure the accuracy of the information in this document, Remee Products Corp. does not guarantee that it is error-free, nor does Remee Products Corp. make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Remee Products Corp. reserves the right to make any adjustments to the information contained herein at any time without notice. Remee Products Corp. expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

Your signature constitutes that you have read and
agreed to this specification sheet and upon confir-
mation of your order; this item may be non-
cancelable and non-returnable.

Signature:

Company:

Date:



Issue Date: 06/15 Revision: 2 All warranty information can be viewed at WWW.REMEE.COM.

This product is RoHS compliant to directive 2002/95/EC.

 1751 State RTE. 17A STE #1 Florida, NY 10921

 Customer Service: 800-431-3864
 Fax: 845-651-4160
 Website: www.remee.com