



MOUNTING INSTRUCTIONS

STEP 1 LOCATING MOUNTING HOLES	STEP 2 INSTALLING ARMATURE PLATE	STEP 3 HEADER MOUNTING PLATE	STEP 4 INSTALLING MAGNET
<p>A. FOLD template at dotted line.</p> <p>B. PLACE bottom portion of template against the door.</p> <p>C. LOCATE and MARK the three (3) holes on the armature plate.</p> <p>D. LOCATE and MARK the two (2) adjustment header plate holes and wire hole on the header mounting plate.</p>	<p>A. DRILL a level 1/4" diameter hole through the door. FOLLOW with a 1/2" diameter drill.</p> <p>NOTE: The following is for a solid door only!</p> <p>B. DRILL two (2) 1/4" holes for the anti-rotation pins 3/4" deep.</p> <p>C. MOUNT the armature plate to the door with the sex bolt.</p> <p>D. PLACE a metal washer, a rubber washer, and a metal washer on the bolt between the door and the armature.</p> <p>E. ENSURE armature rocks on the door.</p>	<p>A. MOUNT header plate to jamb using the two (2) adjustment holes.</p> <p>B. RUN the control cable through the wire hole.</p> <p>C. SLIDE maglock on the header mounting plate.</p> <p>D. ADJUST the position of the maglock to contact the armature.</p> <p>E. REMOVE the maglock and SECURE header mounting plate with the eight (8) remaining screws.</p>	<p>A. SLIDE maglock on the header plate.</p> <p>B. FASTEN maglock to header plate with the Allen head cap screws located at each end of the lock.</p> <p>C. After checking for proper operation and alignment, APPLY THE screw locking agent to the header mounting plate screws, armature, and Allen head cap screws.</p>

Securitron is a brand associated with Hanchett Entry Systems, Inc., an ASSA ABLOY Group company. Copyright © 2016, Hanchett Entry Systems, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of Hanchett Entry Systems, Inc. is prohibited.